Crosswalk between the Bull Trout Matrix and Bull Trout Critical Habitat Primary Constituent Elements

Prepared by:
Jeff Krupka, Karl Halupka, and Judy De La Vergne, CWFO,
March 31, 2011

The purpose of this document is to provide a consistent means for analyzing baseline conditions and project effects to both the bull trout and designated critical habitat for the bull trout using the Matrix of Pathways and Indicators.

The Matrix of Pathway Indicators (Matrix) for bull trout is used to evaluate and document baseline conditions and to aid in making effect determinations for proposed projects (USFWS 1999). The Matrix analysis incorporates 4 population indicators and 19 physical habitat indicators. Analysis of these indicators provides a systematic approach for evaluating the existing baseline condition and potential impacts in terms of metrics meaningful to bull trout.

Designated critical habitat for the bull trout (75 FR 63898) is comprised of nine primary constituent elements (PCEs). These physical, chemical, and biological features correspond to many of the Matrix habitat parameters. Table 1 shows the relationship between the PCEs for bull trout critical habitat and the Matrix habitat indicators. The *refugia* indicator is relevant to all PCEs because in order for the refugia indicator to be rated "functioning appropriately" most if not all of the PCEs must be present. Only one indicator from the population pathways, *persistence and genetic integrity*, applies to evaluation of the condition of PCEs, but this indicator is not depicted in the Crosswalk to simplify Table 1. The following information provides the rationale for how the nine PCEs for bull trout critical habitat can be addressed by using the Matrix indicators (named using italics font).

1. **Springs, seeps, groundwater sources, and subsurface water connectivity (hyporheic flows) to contribute to water quality and quantity and provide thermal refugia.**

   The analysis of *floodplain connectivity* considers the hydrologic linkage of off-channel areas with the main channel and overbank-flow maintenance of wetland function and riparian vegetation and succession. Floodplain and riparian areas provide hydrologic connectivity for springs, seeps, groundwater upwelling and wetlands and contribute to the maintenance of the water table. The *sediment* and *substrate embeddedness* indicators describe the level of fine sediment in the gravel which affects hyporheic flow. Fine sediment fills interstitial spaces making the movement of water through the substrate less efficient. The *chemical contamination/nutrients* and *temperature* indicators evaluate the water quality of groundwater. The *off-channel habitat* indicator suggests how much off-channel habitat is available, and generally off-channels are connected to adjacent

channels via subsurface water. The *change in peak/base flows* indicator considers whether or not peak flow, base flow, and flow timing are comparable to an undisturbed watershed of similar size, geology, and geography. Peak flows, base flows, and flow timing are directly related to subsurface water connectivity and the degree to which soil compaction has decreased infiltration and increased surface runoff. The *drainage network increase* and *road density and location* indicators assess the influence of the road and trail networks on subsurface water connectivity. If there is an increase in drainage network and roads are located in riparian areas, it is likely that subsurface water is being intercepted before it reaches a stream. If groundwater is being intercepted then it is likely that water quality is being degraded through increased temperatures, fine sediment, and possibly chemical contamination. *Streambank condition* addresses groundwater influence through an assessment of stability. The *disturbance history* indicator evaluates disturbance across the watershed and provides a picture of how management may be affecting hydrology. The *riparian conservation areas* indicator determines whether riparian areas are intact and providing connectivity. If riparian areas are intact it is much more likely that springs, seeps, and groundwater sources are able to positively affect water quality and quantity.

2. **Migration habitats with minimal physical, biological, or water quality impediments between spawning, rearing, overwintering, and freshwater and marine foraging habitats, including but not limited to permanent, partial, intermittent, or seasonal barriers.**

   The *physical barriers* indicator provides the most direct assessment of this PCE. Analysis of this indicator includes consideration of whether man-made barriers within the watershed allow upstream and downstream passage of all life stages at all flows. However, some indicators further evaluate physical impediments and others evaluate the biological or water quality impediments that may be present. The *temperature*, *sediment*, *substrate embeddedness*, and *chemical contamination/nutrients* indicators assess whether other barriers may be created, at least seasonally, by conditions such as high temperatures, high concentrations of sediment, or contaminants. The *average wetted width/maximum depth ratio* indicator can help identify situations in which water depth for adult passage may be a problem. A very high average wetted width/maximum depth value may indicate a situation where low flows, when adults migrate, are so spread out that water depth is insufficient to pass adults. The *change in peak/base flows* indicator can help determine if change in base flows have been sufficient to prevent adult passage during the spawning migration. The *persistence and genetic integrity* indicator addresses biological impediments by evaluating negative interactions (e.g., predation, hybridization, and competition) with other species.

3. **An abundant food base, including terrestrial organisms of riparian origin, aquatic macroinvertebrates, and forage fish.**

   None of the indicators directly address this PCE, but a number of them address it indirectly. The *sediment* and *substrate embeddedness* indicators document the extent to which substrate interstitial spaces are filled with fine sediment. Interstitial

spaces provide important habitat for aquatic macroinvertebrates, sculpin, and other substrate-oriented prey which are important food sources for bull trout. The *chemical contamination/nutrients* indicator evaluates the level to which a stream is contaminated by chemicals or has a high level of nutrients. Chemicals and nutrients greatly affect the type and diversity of aquatic invertebrate communities present in a water body. The *large woody debris* and *pool frequency and quality* indicators assess habitat complexity. High stream habitat complexity is associated with diverse and abundant macroinvertebrate and fish prey. The *off-channel habitat* and *floodplain connectivity* indicators document the presence of off-channels which are generally more productive than main channels. Off channel areas are important sources of forage, particularly for juveniles. The *streambank condition* and *riparian conservation areas* indicators both shed light on the very basis of the food base of a stream. Vegetation along streambanks and in riparian areas provide important habitat for terrestrial macroinvertebrates that can fall into the water as well as sources of nutrient inputs that support aquatic invertebrate production.

4. **Complex river, stream, lake, reservoir, and marine shoreline aquatic environments and processes that establish and maintain these aquatic environments, with features such as large wood, side channels, pools, undercut banks and unembedded substrates, to provide a variety of depths, gradients, velocities, and structure.**

   Several indicators address this PCE directly. The *sediment* and *substrate embeddedness* indicators provide insight into how complex substrates are within a stream by documenting percent fines and embeddedness. As percent fines and embeddedness increase, substrate complexity decreases. The *large woody debris* indicator provides an excellent picture of habitat complexity. The indicator rates the stream based on the amount of in-channel large woody debris. Habitat complexity increases as large wood increases. The *pool frequency and quality* and *large pools* indicators address habitat complexity by rating the stream based on the frequency of pools and their quality. Habitat complexity increases as the number of pools and their quality increase. The *off-channel habitat* indicator directly addresses complexity associated with side channels. The indicator is rated based on the amount of off-channel habitat, cover associated with off-channels, and flow energy levels. *Average wetted width/maximum depth ratio* is an indicator of channel shape and pool quality. Low ratios suggest deeper, higher quality pools. The *streambank condition* and *riparian conservation areas* indicators both shed light on the complexity of river and stream shorelines. Vegetation along streambanks and in riparian areas provides important habitat complexity and channel roughness. The *streambank condition* indicator also provides information about the capacity of an area to produce undercut banks, which can be a very important habitat feature for bull trout. The *floodplain connectivity* indicator addresses complexity added by side channels and the ability of floodwaters to spread across the floodplain to dissipate energy and provide access to high-flow refugia for fish. The *road density and location* indicator addresses complexity by identifying if roads are located in valley bottoms. Roads located in valley bottoms reduce complexity by eliminating vegetation and replacing complex habitats with riprap or fill, and often confine the floodplain. The *disturbance regime* indicator documents

the frequency, duration, and size of environmental disturbance within the watershed. If scour events, debris torrents, or catastrophic fires are frequent, long in duration, and large, then habitat complexity will be greatly reduced.

5. **Water temperatures ranging from 2 to 15 °C (36 to 59 °F), with adequate thermal refugia available for temperatures that exceed the upper end of this range. Specific temperatures within this range will depend on bull trout life-history stage and form; geography; elevation; diurnal and seasonal variation; shading, such as that provided by riparian habitat; streamflow; and local groundwater influence.**

   The *temperature* indicator addresses this PCE directly. The indicator rates streams according to how well temperatures meet bull trout requirements. Other matrix indicators address temperature indirectly. The *off-channel habitat* and *floodplain connectivity* indicators address how well stream channels are hydrologically connected to off-channel areas. Floodplains and off-channels are important to maintaining the water table and providing connectivity to the channel for springs, seeps, and groundwater sources which contribute cool water to channels. The *average wetted width/maximum depth ratio* indicator also corresponds to temperature. Low width to depth ratios indicate that channels are narrow and deep with little surface area to absorb heat. The *streambank condition* indicator documents bank stability. If the streambanks are stabilized by vegetation rather than substrate then it is likely that the vegetation provides shade which helps prevent increases in temperature. The *change in peak/base flows* indicator evaluates flows and flow timing characteristics relative to what would be expected in an undisturbed watershed. If base flow has been reduced, it is likely that water temperature during base flow has increased since the amount of water to heat has decreased. The *road density and location* and *drainage network increase* indicators documents where roads are located. If roads are located adjacent to a stream then shade is reduced and temperature is likely increased. Roads also intercept groundwater and can reduce this cooling influence, as well as discharge typically warmer stormwater. The *disturbance history* indicator describes how much of the watershed has been altered by vegetation management and therefore indicates how much shade has been removed. The *riparian conservation areas* indicator addresses stream shade which keeps stream temperatures cool. The presence of *large pools* may provide thermal refugia when temperatures are high.

6. **In spawning and rearing areas, substrate of sufficient amount, size, and composition to ensure success of egg and embryo overwinter survival, fry emergence, and young-of-the-year and juvenile survival. A minimal amount of fine sediment, generally ranging in size from silt to coarse sand, embedded in larger substrates, is characteristic of these conditions. The size and amounts of fine sediment suitable to bull trout will likely vary from system to system.**

   The *sediment* and *substrate embeddedness* indicators directly address this PCE. These indicators evaluate the percent fines within spawning areas and the percent embeddedness within rearing areas. The *streambank condition* and *riparian conservation areas* indicators indirectly address this PCE by documenting the presence or lack of potential fine sediment

sources. If streambanks are stable and riparian conservation areas are intact then there is a low risk of introducing fine sediment from bank erosion. Also, the *floodplain connectivity* indicator indirectly addresses this PCE. If the stream channel is connected to its floodplain, then there is less risk of bank erosion during high flows because stream energy is reduced as water spreads across the floodplain. The *increase in drainage network* and *road density and location* indicators assess the effects of roads on the channel network and hydrology. If the drainage network has significantly increased as a result of human-caused disturbance or road density is high within a watershed and roads are located adjacent to streams, then it is likely that in-channel fine sediment levels will be elevated above natural levels. The *disturbance regime* indicator documents the nature of environmental disturbance within the watershed. If the disturbance regime includes frequent and unpredictable scour events, debris torrents, and catastrophic fire, then it is likely that fine sediment levels will be elevated above background levels. A consideration for all indicators directly or indirectly influencing this PCE is that it is desirable to achieve an appropriate balance of stable areas to provide undercut banks and eroding areas that are sources for recruiting new spawning gravels. Too little sediment in a stream can also be detrimental.

7. **A natural hydrograph, including peak, high, low, and base flows within historic and seasonal ranges or, if flows are controlled, minimal flow departure from a natural hydrograph.**

   The *change in peak/base flows* indicator addresses this PCE directly by documenting the condition of the watershed hydrograph relative to an undisturbed watershed of similar size, geology, and geography. There are several indicators that address this PCE indirectly. The *streambank condition* indicator documents bank stability. If the streambanks are stabilized by vegetation rather than substrate then it is likely that the streambank can store water during moist periods and releases that water during dry periods which contributes to water quality and quantity. The *floodplain connectivity* indicator is relevant to water storage within the floodplain which directly affects base flow. Floodplains are important to maintaining the water table and providing connectivity to the channel for springs, seeps, and groundwater sources which contribute to water quality and quantity. The *increase in drainage network* and *road density and location* indicators assess the influence of the road and trail networks on hydrology. If there is an increase in drainage network and roads are located in riparian areas, it is likely is being intercepted and quickly routed to a stream which can increase peak flow. The *disturbance history* indicator evaluates disturbance across the watershed and provides a picture of how management may be affecting hydrology; for example, it may suggest the degree to which soil compaction has decreased infiltration and increased surface runoff. The *riparian conservation areas* indicator determines whether riparian areas are intact, functioning, and providing connectivity. If riparian areas are intact it is much more likely that springs, seeps, and groundwater sources are able to positively affect water quality and quantity.

8. **Sufficient water quality and quantity such that normal reproduction, growth, and survival are not inhibited.**

This PCE is closely related to PCE 7, with PCE 8 adding a water quality component (i.e., there is a high level of overlap in indicators that apply to both PCEs 7 and 8). The *temperature* and *chemical contamination/nutrients* indicators directly address water quality by comparing water temperatures to bull trout water temperature requirements, and documenting 303(d) designated stream reaches. Several other indicators indirectly address this PCE by evaluating the risk of fine sediment being introduced that would result in decreased water quality through increased turbidity. The *streambank condition* and *riparian conservation areas* indicators indirectly address this PCE by documenting the presence or lack of potential fine sediment sources. If streambanks are stable and riparian conservation areas are intact then there is a low risk of introducing fine sediment from bank erosion. Also, the *floodplain connectivity* indicator indirectly addresses this PCE. If the stream channel is connected to its floodplain, then there is less risk of bank erosion during high flows because stream energy is reduced as water spreads across the floodplain. *Average wetted width/maximum depth ratio* is an indication of water volume, which indirectly indicates water temperature, (i.e., low ratios indicate deeper water, which in turn indicates possible high-flow refugia). This indicator in conjunction with *change in peak/base flows* is an indicator of potential water quality and quantity deficiencies, particularly during low flow periods. The *increase in drainage network* and *road density and location* indicators assess the effects of roads on the channel network and hydrology. If the drainage network has significantly increased as a result of human-caused disturbance or road density is high within a watershed and roads are located adjacent to streams, then it is likely that suspended fine sediment levels will be elevated above natural levels. If roads are located adjacent to a stream then shade is reduced and temperature is likely increased. Roads also intercept groundwater and can reduce this cooling influence, as well as discharge typically warmer stormwater. The *disturbance regime* indicator documents the nature of environmental disturbance within the watershed. If the disturbance regime includes frequent and unpredictable scour events, debris torrents, and catastrophic fire, then it is likely that turbidity levels will be elevated above background levels.

9. Sufficiently low levels of occurrence of nonnative predatory (e.g., lake trout, walleye, northern pike, smallmouth bass); interbreeding (e.g., brook trout); or competing (e.g., brown trout) species that, if present, are adequately temporally and spatially isolated from bull trout.

The only indicator that directly addresses this PCE is the *persistence and genetic integrity* indicator. This indicator addresses the likelihood of predation, hybridization, or displacement of bull trout by competitive species. The *temperature* indicator can provide indirect insights about whether conditions are conducive to supporting “warm water” species.

Table 1. Relationship of the Matrix Indicators to the Primary Constituent Elements of Bull Trout Critical Habitat

Pathways (bold) and Indicators	**PCE 1 - Springs, Seeps, Groundwater**	**PCE 2- Migratory Corridors***	**PCE 3 - Abundant Food Base**	**PCE 4 - Complex Habitats**	**PCE 5 - Temperature**	**PCE 6 - Substrate**	**PCE - 7 Hydrograph**	**PCE 8 - Water Quality/ Quantity**	**PCE 9 - Nonnative Species***
Water Quality									
Temperature	X	X			X			X	X
Sediment	X	X	X	X		X			
Chemical Contamination/Nutrients	X	X	X					X	
Habitat Access									
Physical Barriers		X							
Habitat Elements									
Substrate Embeddedness	X	X	X	X		X			
Large Woody Debris			X	X					
Pool Frequency and Quality			X	X					
Large Pools				X	X				
Off-Channel Habitat	X		X	X	X				
Refugia	X	X	X	X	X	X	X	X	X
Channel Conditions and Dynamics									
Wetted With/Max. Depth Ratio		X		X	X			X	
Streambank Condition	X		X	X	X	X	X	X	
Floodplain Connectivity	X		X	X	X	X	X	X	
Flow/Hydrology									
Changes in Peak/Base Flows	X	X			X		X	X	
Drainage Network Increase	X				X	X	X	X	
Watershed Conditions									
Road Density and Location	X			X	X	X	X	X	
Disturbance History	X				X		X		
Riparian Conservation Areas	X		X	X	X	X	X	X	
Disturbance Regime				X		X		X	

* = PCE is also related to the population pathway, *persistence and genetic integrity* indicator